

# cam dock 50/75

flexible adaptations to test heads

precise docking

repeatable docking procedure

fully inTEST compatible



## cam dock

low cost compatible docking solution

### key features

high docking force  
compatible to existing solutions with improved robust design  
low maintenance  
modular design  
no breaking or stretching cables

### specifications

docking travel: 12 mm  
unevenness compensations: 5 mm

cam dock 50: 2000 N docking force  
cam dock 75: 3000 N docking force

repeatable accuracy in x&y: 0.05 mm  
repeatable accuracy in z: 0.05 mm

free position of locking lever



### typical adaptations

credence: d40, d10  
eagle test systems: ETS 300, ETS 364  
LTX CX, EX, MX, LX, Synchro HT  
teradyne Catalyst, J750,  
MicroFlex

subject to technical change  
without prior notice  
© 2007



S2/S8  
conform



**esmo**

esmo ag phone +49-8031-233 88 0  
brückenstrasse 1 fax +49-8031-233 88 10  
d-83022 rosenheim sales@esmo-ag.com  
germany www.esmo-ag.com

esmo asia pte. ltd. phone +65-6562-8833  
25 international business park fax +65-6562-8860  
#03-112 german centre sales@esmo-asia.com  
singapore 609916 www.esmo-ag.com

esmo usa inc. phone +1-408-982 9911  
3350 scott blvd., suite #6102 fax +1-408-982 9933  
santa clara, ca 95054 sales@esmo-usa.com  
usa www.esmo-ag.com