
# docking + interfacing



cold test cover EVOLUTION
saving cost,
minimizing downtime



# key features

(r)evolutionary state-of-the-art docking and handler chamber sealing solution

intuition-based, technologically advanced design novelty

universal tester/handler compatibility

compatibility with third-party dockings will be verified at request

protection against CUH/handler chamber icing

operating temperature ranging from -50 °C to +150 °C (-58 °F to +302 °F)

reverting system conducting purge air back into handler chamber + dual-sealing plate

cold test cover assembly permanently attached to handler

docking and alignment features integrated into cold test cover assembly

test cell servicing with closed sealing cover for up to 30 minutes

automatic or mechanical push-button system operation options

cost-/time-saving + yield-/quality-increasing operation features

durable and robust design

single module or integrated dib-changing solution

optional product features and upgrade integrations:

- sensor-controlled temperature detection + cold temperature guard/alarm system
- integrated dib-changing solution:
  - odib exchange time of less than 1 minute
  - o side-mapping
  - touch panel operation
  - o programmable user interface
  - o individual, password-protected control options





S2/S8





## esmo Germany Rosenheim

esmo AG Brueckenstrasse 1 83022 Rosenheim Germany

Phone +49 (8031) 233 88 0 Fax +49 (8031) 233 88 10 sales@esmo-ag.com

#### esmo USA Sacramento

esmo USA Corp. 1020 Winding Creek Road Suite #120 Roseville, California 95678

Phone +1 (916) 307 6345 Fax +1 (916) 307 6341 sales@esmo-usa.com

# esmo Singapore Singapore

esmo Asia Pte. Ltd. 115 Eunos Avenue 3 #05-03 Singapore 409839 Singapore

Phone +65 (656) 288 57 Fax +65 (656) 288 60 sales@esmo-asia.com

## esmo China Shanghai

esmo Asia North Co. Ltd. Building 2, No. 388 Xinrun Road Xin Qiao Industrial Zone Song Jiang District 201612 Shanghai China

Phone +86 (21) 5768 7228 + ext. 201 Fax +86 (21) 5768 7132 info@esmo-ag.com.cn